



Servizi
Rappresentanze
Consulenza
Progettazione
Produzione
Forniture

ELGA di Gallione Franco
via del Giglio n°65/B
55049 Viareggio (LU) ITALIA
tel. +39 0584 944868
fax. +39 0584 944851
E-mail: fgallione@tiscali.it

web: www.elgaitalia.com - Codice NATO Costr: / Forn. (N/CAGE): **AD 010**
P.IVA 01868240464 - Cod. Fisc. GLL FNC 53P02 L833R - Iscr. C.C.I.A.A. Lucca n°177644

Mil-Std. Waterproof Case 5 3I-4214-5B-L

Mil-Std. Waterproof Case 6 3I-5014-6B-L



Mil-Std. Waterproof Case 5

Mil-Std. Waterproof Case 5
 3I-4214-5B-L
 Category: Mil Std Waterproof
 Series: 3I Series Cases



SKB 3I Series Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasketed, water and dust tight, submersible design (MIL-C-4150J) that is resistant to corrosion and impact damage. Features a molded-in hinge, patent pending "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD-648C), resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD-810F).

[Read the Certified 3I Series Waterproof Test \(PDF\)](#)
[Read the Certified 3I Series Drop Test \(PDF\)](#)

Features layers of cubed foam for customer customization and the padlock holes include stainless steel protector clips for added strength.

- In-line skate style wheels for easy transport
- Trigger release latches can be retrofitted with TSA accepted key locking latches
- Padlock holes include stainless steel padlock protector clips
- Layers of foam for customization
- Cushion grip handles on three sides
- Waterproof and dust tight design (MIL-C-4150J)
- Molded-in hinge for added protection
- Trigger release latch system
- Snap-down rubber over-molded cushion grip handle
- Ambient pressure equalization valve (MIL-STD-648C)
- Resistant to UV, solvents, corrosion, fungus (MIL-STD-810F)
- Resistant to impact damage (MIL-STD-810F)

Specifications

Features
ATA Rated
Waterproof
Accepts TSA Latches
Built-in Tow Handle
Layered Foam
Certifications
MIL-STD-810F
MIL-STD-C-4150J
MIL-STD-648C
IP67
Process
Injection Molded

WEIGHT		
Shipping Weight	22.40	10.16 kg
INSIDE DIMENSIONS		
Lid Depth	1.50 in	3.81 cm
Base Depth	4.00 in	10.16 cm
Interior Length	42.50 in	107.95 cm
Interior Width	14.50 in	36.83 cm
Interior Depth	5.50 in	13.97 cm
Interior Cu. Volume	1.96 cu ft	0.06 cu m
OTHER PROPERTIES		
Color	0	0
Max. Temperature	210.00° F	98.89° C
Min. Temperature	-40.00° F	-40.00° C

Mil-Std. Waterproof Case 6

Mil-Std. Waterproof Case 6
 3i-5014-6B-L
 Category: Mil Std Waterproof
 Series: 3i Series Cases



SKB 3i Series Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasketed, water and dust tight, submersible design (MIL-C-4150J) that is resistant to corrosion and impact damage. Features a molded-in hinge, patent pending "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD-648C), resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD-810F).

[Read the Certified 3i Series Waterproof Test \(PDF\)](#)
[Read the Certified 3i Series Drop Test \(PDF\)](#)

- Layered foam
- Reinforced locking loops for customer supplied locks
- Rubber over-molded cushion grip carrying handle and pull handle
- Convenient quiet-glide wheels

- Trigger release latch system
- Snap-down rubber over-molded cushion grip handle
- Ambient pressure equalization valve (MIL-STD-648C)
- Resistant to UV, solvents, corrosion, fungus (MIL-STD-810F)
- Resistant to impact damage (MIL-STD-810F)

Specifications

Features
ATA Rated
Waterproof
Built-in TSA Latches
Built-in Wheels or Casters
Built-in Tow Handle
Layered Foam
Certifications
MIL-STD-810F
MIL-STD-C-4150J
MIL-STD-648C
IP67
Process
Injection Molded
Material
PP

WEIGHT		
Shipping Weight	24.85	11.27 kg
INSIDE DIMENSIONS		
Lid Depth	1.50 in	3.81 cm
Base Depth	4.50 in	11.43 cm
Interior Length	50.50 in	128.27 cm
Interior Width	14.50 in	36.83 cm
Interior Depth	6.00 in	15.24 cm
Interior Cu. Volume	2.54 cu ft	0.07 cu m
OUTSIDE DIMENSIONS		
Exterior Length	53.04 in	134.72 cm
Exterior Width	16.98 in	43.13 cm
Exterior Depth	6.84 in	17.37 cm
Exterior Cu. Volume	3.56 cu ft	0.10 cu m
OTHER PROPERTIES		
Color	0	0
Max. Temperature	210.00° F	98.89° C
Min. Temperature	-40.00° F	-40.00° C
SHIPPING CUBE		
Shipping Carton Length	53.13 in	134.94 cm
Shipping Carton Width	17.25 in	43.82 cm
Shipping Carton Height	7.00 in	17.78 cm