

Presenti su Mercato Elettronico della P.A.

web: [www.elgaitalia.com](http://www.elgaitalia.com) - socio CEI 05085 - Codice NATO Costr: / Forn. (N/CAGE): **AD 010**

P.IVA 01868240464 - Cod. Fisc. GLL FNC 53P02 L833R - Iscr. C.C.I.A.A. Lucca n°177644

Magazzino - Officina - Tel./Fax. +39 0584 617951 - via Mincio n° 67 - 55043 Lido di Camaio (LU)

## S.T. Lampada a batteria ricaricabile ATEX

### Unit Dimensions

Length: 11 in.

Width: 4 in.

Height: 12 in.

### Master Pack Dimensions

Weight: 12 lbs.

Cube Dimensions: 14.5 in x 11.5 in x 13 in

Quantity: 3

### Specifications

Ni-Cad Battery: 4.8 V, 1.6 Ah

Power Sources options: 120V or 220V AC  
12-24V DC

Weight: (w/ Alkaline Batteries): 1 lb.

Weight: (w/ Ni-Cad Battery Pack): 1lb

Bulb/Lamp Life: 50 hours

Light Output: 45,000 beam candlepower

### Components

Super Tough Nylon Housing

Microprocessor Controlled Circuit Board

w/ LED Status Indication

Co-Axial AC Power Pack

Automotive DC Power Cord

### Safety Certifications:

UL: Class I, Div 1, Group D

Operating Temp T3

ATEX II 2 G EEX ib e IIB T3

### Product Features

DC Input: 12/24V DC Vehicular Adapter (Fire Trucks)

AC Input: 120V AC Adapter (US/North America) 220-240V AC Adapter (Euro or UK)

- Flashlight Receives Priority Charge

- Wall & Vehicle Mountable

- Microprocessor Controlled

- Super Tough Nylon

- LED Status Indication

RED: Charging

GREEN: Fully Charged

AMBER: Standby

FLASHING RED: Fault

- 2-Hour Charging Time

- Safe to Touch Charging Contacts

