

## MM series Mini



Maximum output of 56 m<sup>3</sup> / 2,000 ft<sup>3</sup> per minute

## MM series Mega



Maximum output of 150 m<sup>3</sup> / 5,000 ft<sup>3</sup> per minute

## OPTIONS AND ACCESSORIES

Remote control timer  
Program your fog emission  
from  
in advance



DMX interface  
Operate the fogger  
your lighting desk



Flight case  
Durable for safe  
and easy transport.



FLUID MDG Neutral Fluid  
Safe, non-toxic. Available  
in 2.5 L (0.66 US gallon),  
20 L (5.3 US gallon) and  
205 L (55 US gallon) sizes.



## Technical data

## MM series

	Mini	Mega
Maximum fog output per minute	56 m <sup>3</sup> (2,000 ft <sup>3</sup> )	150 m <sup>3</sup> (5,000 ft <sup>3</sup> )
Fluid consumption per hour (full volume)	1.5 L (34 oz)	3.5 L (118 oz)
Fluid Capacity	2.5 L (0,66 US gallon)	5 L (1.32 US gallon)
Fog colour	Pure white	Pure white
Particle size	1-3 microns	1-3 microns
Warm-up time (maximum)	8 minutes	8 minutes
Fluid type (M.S.D.S. available on request)	MDG Dense,Low, Fog, Or WB2 Fluid	MDG Dense,Low, Fog, Or WB2 Fluid
Operating Voltage	115 or 230VAC 50/60Hz	115 or 230VAC 50/60Hz
Power consumption	715 W	1.415 W
Dimensions Length	49 cm (19")	49 cm (19")
Width	23 cm (9")	28 cm (11")
Height	25 cm (10")	25 cm (10")
Weight	12 kg (25 lb)	16 kg (35 lb)
Shipping weight (with flight case)	23 kg (50 lb)	27 kg (60 lb)
Approval	CE approved, CSA and UL pending	CE approved, CSA and UL pending